

## Boone Docking Station

Rev. Date: 20 June 2007

### Tech Spec's

- Unique side-loading design makes mounting the most cumbersome racks a snap.
- Equipped with 2 quick-loading Dock Blocks the Docking Station provides attachment points for 4 racks or draw bars.
- 6 Dock Block locations allow customization and the addition of more Dock Blocks for additional gear storage.
- 300 lb. load capacity (150 lb. max per Dock Block)
- Use your cargo carrier as a shelf in the garage!
- Transform your bike rack into garage bike storage.
- Upper end quickly screws to a wall while the foot of the unit rests on the floor.
- Brackets for all your cargo straps, bungee cords and trailer balls
- Models available for 2" and 1 ¼" hitches, **Also fits racks with shoulder pins (i.e. Saris, Yakima and Thule)**
- Constructed of tough, powder coated carbon steel
- 48" tall and extends 11" from the wall
- Weighs 13 lbs.

### Use and Mounting Tips

Before mounting your Boone Docking Station take into consideration what gear will be stored on the unit and how often it will be used.

Hitch-mounted gear is easily attached to the Docking Station by slipping the hole for the hitch pin onto a Docking Station Locating Pin and allowing the square tube of the gear to rest on top of the Dock Block round tube. Secure your gear to the Docking Station by inserting a Bridge Pin into the through hole in the Locating Pin.

- **Bike Racks**
  - Use your hitch-mounted rack as a garage bike rack when stored on the Docking Station.
  - If storing multiple pieces of gear, determine the location for the bike rack first.
  - If storing bikes on the bike rack, allow 6' of horizontal space (3' each side of Docking Station).

- For frequent use, it is generally easier to mount a bike rack on one of the lowest Dock Block settings (you won't need to lift the bikes as high).
- If a higher Dock Block mounting is desired, mount the Docking Station away from garage door tracks. Bikes will interfere with door tracks at the highest Dock Block location.
- Cargo carriers
  - In a horizontal position, use a cargo carrier as light-duty shelving.
  - For storing in a horizontal position, a higher Dock Block position is desirable.
  - For storing in a vertical position, hang the carrier from a Locating Pin. A mid-height Dock Block location is desirable to give adequate floor and wall clearance for the carrier.
- Draw bars
  - Store either in a horizontal or vertical position (simply hanging from a Locating Pin).
  - If storing multiple pieces of gear, determine the location for the draw bar(s) last. It's easier to find a good location for smaller gear.
- Use the Strap Brackets to hang bungee cords, nylon straps or anything with a hook. Smaller trailer balls with a  $\frac{3}{4}$ " threaded shank can be stored on the Strap Brackets by inserting the threaded shank through one of the holes and threading the nut on the back side.